

Lovibond® Colour Measurement Tintometer® Group



RT505 (diffuse/8) 4 mm aperture

Portable Sphere Spectrophotometer for Multiple Applications



- Sphere Technology with 4 mm Measurement Area / 6.5 mm Target Window
- Ability to Output Simultaneous SPIN, SPEX and Correlated Gloss Measurements
- Access to up to 4,000 Reference Samples for Fast Access to Existing Data
- Fully Portable with Optional Dual-Bay Charging

Part Number: 400504

Capable and Flexible

The 4 mm measurement aperture and the ability to output simultaneous SPIN, SPEX and Correlated Gloss measurements makes the RT 500 instrument extremely flexible.

You can use it in production or in the field to take quick colour measurements and compare the accuracy with proven results - not guess work from visual comparison. It is equally applicable for reflective measurements or uneven surfaces.

Hands-Free Measurement

The remote measurement trigger enables you to operate the instrument remotely.

Storage

The instrument provides access to up to 4,000 reference samples which have been stored for fast access to existing data.

Ideal for Off-Site Measurements

The RT 500 is ideal for use in the field. The optional dual-bay charging facility helps you increase your instrument's up-time by letting you simultaneously charge the second battery.

Ensures Your Brand Identity

If you are using metallics, special finishes and textures to gain market presence, your brand must be important to you. Colour measurement throughout your production process results in your end products always looking the same and building on your quality brand.

Enhanced Quality Software Control

The RT 505 can be combined with the OnColor™ software package allowing you to download measurement data, analyse in detail and store indefinitely on a PC.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

Application

Chemicals | Coatings | Food and Beverage | Household Products | Medical and Clinical Products | Pharmaceuticals and Cosmetics | Plastics | Textiles

RT505 (diffuse/8) 4 mm aperture

Portable sphere spectrophotometer with extreme flexibility for multiple applications. An ideal mid-range solution if you are looking for accurate colour measurement.

Technical Data

Applicable Standard	ASTM 313 ASTM D1925 ASTM E308
Colour Type	Transparent Translucent Opaque
Spectral Interval	10 nm - measured; 10nm - output
Measurement Range	0 tot 200 % reflectie
Measurement Time	Approx 2 seconds
Lamp Life	Approx 500,000 measurements
Storage Temperature	-4 to 122°F (-20° to 50°C)
Spectral Range	400 - 700 nm
Portability	Benchtop

Delivery Scope

- Sturdy Box Including
- Instrument
- Calibration box
- Universal power supply
- Instruction manual

Accessories

Title	Part Number
RT On-Colour Premium Software	400610
RT300/400/500 Benchtop Stand	400620
RT300/400/500 Lqd Cell Holder	400630
RT300/400/500 Powder Cell Holder	400640
RT300/400/500 Pellet Holder	400680

Tintometer GmbH
Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
Fax: +49 (0)231/94510-30
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited
Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China
Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia
Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil
Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Inc.
6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.com
USA

Tintometer India Pvt. Ltd.
Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@tintometer.com
www.lovibondwater.in
India

Tintometer Spain
Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies